

Pattern Gal Express

www.aPatternGal.com
3735 W. 1000 N. Tremonton, UT 84337
Designs & Patterns by Melanie Capener


© 2004, RaMel Enterprises, Inc. These instructions are for personal use only and are part of a kit. No part may be used for profit without prior written permission.

2005 Row 4b


Block 5

Bright Hopes House

12" finished block, 12 1/2" unfinished block.



- Sew seams away from the center piece.
- Sew scant 1/4" seam allowances, do not open seams.
- Lay out block pieces as cut, following diagram if necessary.
- Dry Press seams away from center. Move iron in one direction only, lift and press from center out to edges. Never iron back and forth, you are pressing seams not ironing wrinkles. Do not use steam until block is finished, water resets and distorts natural cotton fibers.
- Chain-sew when possible and use an anchor or tail to prevent thread nesting on bobbin side.



Colors & Size of pieces: Cutting measurements

Half Row 4: Make 3 blocks

- A. Black = 1 square 4 1/8". 1 Block = 4.25" sq.;
Blocks: 2 = 4.25" x 9"; **4 = 9" x 21" fat qtr.**; **6 = 4.25" x 26"**; 7 = 1/8 yd.
- B. Yellow = 3 squares 4 1/8". 1 Block = 4.25" x 14";
Blocks: 2 = 4.25" x 28"; **4 = 9" x 28"**; **6 = 1/4 yd**; 7 = 14" x 42"
- C. Red = 1 strip 1.75" x 44" = 4 (C1), 1 3/4" x 4 1/8" and 4 (C2), 1 3/4" x 6 1/2"
Blocks: 1 = 1.75" x 44"; 2 = 3.5" x 44"; **4 = 7" x 44"** **5 = 1/4 yd**; 7 = 14" x 44"
- D. Green = 1.75" x 21" = 4, 1.75" x 5.25" strips
Blocks: 1 = 1.75" x 21"; 2 = 1.75" x 44"; **4 = 4" x 44"**, **5 = fat 1/8**, 7 = 1/4 yd.
- E. Blue = 1.75" x 21" = 4, 1.75" x 5.25" strips
Blocks: 1 = 1.75" x 21"; 2 = 1.75" x 44"; **4 = 4" x 44"**, **5 = fat 1/8**, 7 = 1/4 yd.

Assembly

- Log Cabin Strip Method, 4 pieces around center.
1. Cut center squares 1 A (Black) and 4B (Yellow). 4 1/8"
 2. Log Cabin Strip Method Block Placement
 - a. Place C1 strip face up on machine. Lay each of four center squares face down on strip.
 - b. Butt each piece of fabric next to the previous fabric square.
 - c. Tighten stitch length or back stitch three stitches at the beginning and ending of each new fabric square. Sew seams away from center.
 - d. Carefully cut in between each block down the length of strip.
 - e. Place next strip to be sewn face up in front of you on machine.
 - f. Open block seam and place last piece sewn on the top edge of strip face down.
 3. Sew strips in the following order
 - a. Center & C1, D, E, and sew C2 last.
 4. Press seams away from the center.
 5. Follow Diagram and sew four patch together.
 - a. Sewing 2 squares together and then each half together.

Quilt Row Assembly

Attach Black Roof top point (Row 3) to the top of these 4 blocks to make an 18.5" x 12.5" unfinished block. Do not assemble row 3-4 until each unit is combined to make larger blocks.

NOTES: