



Pattern Gal Express

www.aPatternGal.com
3735 W. 1000 N. Tremonton, UT 84337
Designs & Patterns by Melanie Capener


© 2004, RaMel Enterprises, Inc. These instructions are for personal use only and are part of a kit. No part may be used for profit without prior written permission.

2005 Row 7

Block 9

Flying Geese Pinwheel

12" finished block, 12 1/2" unfinished block.





- Sew seams away from the center piece.
- Sew scant 1/4" seam allowances, do not open seams.
- Lay out block pieces as cut, following diagram if necessary.
- Dry Press seams away from center. Move iron in one direction only, lift and press from center out to edges. Never iron back and forth, you are pressing seams not ironing wrinkles. Do not use steam until block is finished, water resets and distorts natural cotton fibers.
- Chain-sew when possible and use an anchor or tail to prevent thread nesting on bobbin side.

Colors & Size of pieces: Cutting measurements

Half Row 7: Make 4 blocks

- A. Cream = 4 rectangles 3 1/2" x 6 1/2",
Blocks: 1 = 3.5" x 28", 2 = 7 x 28" 4 = 1/3 yd; 7 = 2/3 yd
- B. Light Blue = 4 rectangles 3 1/2" x 6 1/2".
Blocks: 1 = 3.5" x 28", 2 = 7 x 28" 4 = 1/3 yd; 7 = 2/3 yd
- C. Blue = 8 squares 3 1/2",
Blocks: 1 = 3.5" x 28", 2 = 7" x 28", 4 = 1/3 yd; 7 = 2/3 yd



Assembly

Make 4 flying geese. Using the Stitch & Flip Method

1. Cut out all "C" squares.
 - a. Draw lines down center diagonal of all 3 1/2" squares. (Draw extra 1/2" line away from center to save time and fabric scraps).
2. Sew 4 BC regular flying geese, using B rectangle and C squares.
 - a. Sew down each drawn line and trim away extra leaving 1/4" seam allowance.
 - b. Sew on the right hand corner make half goose. Finger press seam away from goose point. And sew left side of goose on. This makes the top of 4-patch.
 - c. Press if desired.
3. Sew flying goose segments to A strip.
 - a. Place A strip face up on machine next to pressure foot. Place flying goose segment face down on strip with point closest to machine.
 - b. Butt each piece of fabric next to the previous fabric square.
 - c. Tighten stitch length or backstitch three stitches at the beginning and ending of each new fabric square. Sew seams away from center.
 - d. Carefully cut in between each block down the length of strip.
4. Press seams toward outside edges away from points.
5. Lay out block according to diagram and sew 2 squares together to create half block.
 - a. Sew block halves together.

Quilt Row Assembly

Sew Flying Goose Pinwheels (4) Block 9 and Colorado (3) Block 10 together to make 12.5" x 84.5" unfinished Row 7. Assemble rows as desired or in order of quilt.

NOTES: